

TECHNICAL DATA SHEET

CN104B80Z

Epoxy acrylate blended with HDDA (SR238)

DESCRIPTION

CN104B80Z is a difunctional bisphenol A based epoxy acrylate blended with 20% SR238, hexane diol diacrylate. It provides a good balance of water properties and high reactivity. The base oligomer, CN104, offers the lowest color of Sartomer's bisphenol A based epoxy acrylates.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Color (Gd)	<3
Viscosity at 25°C (mPa.s or cPs)	13200
Density at 25°C (g/mL)	1.5405
Refractive Index at 25°C	1.531

CURED PROPERTIES

Tg (°C), by DSC	69
Young Modulus (MPa)	1655
Elongation at break (%)	5
Tensile Strength (MPa)	61

PRODUCT PERFORMANCE

Chemical Resistance
Hardness
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
PE/PET/PP/PMMA Adhesion
Moisture Resistance
Corrosion Resistance
Scratch Resistance

SUGGESTED APPLICATIONS

Offset inks
Overprint varnishes

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com