SARTOMER®

TECHNICAL DATA SHEET

CN120D80

Epoxy Acrylate blended with GPTA (SR9020)

CN120D80 is a difunctional bisphenol A based epoxy acrylate blended with 20% SR9020, glyceryl propoxy triacrylate. It provides a good balance of water properties and high reactivity. CN120 offers the lowest viscosity of Sartomer's bisphenol A based epoxy acrylates.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance Clear liquid Functionality Color (Gd) Density at 25°C (g/mL) 1.1413 Refractive Index at 25°C 1.5359

CURED PROPERTIES

Tg (°C), by DSC 80 Young Modulus (MPa) 1868 Elongation at break (%) Tensile Strength (MPa) 57

PRODUCT PERFORMANCE

Wood Adhesion ARS/PC Adhesion Metal Adhesion PVC/PS Adhesion PE/PET/PP/PMMA Adhesion Chemical Resistance Hardness Scratch Resistance Abrasion Resistance Moisture Resistance Corrosion Resistance Shrinkage

SUGGESTED APPLICATIONS

Adhesives & sealants Electronics Flexographic inks Metal coatings Wood coatings

Arkema Inc 502 Thomas Jones Way Exton, PA 19341 – AMERICA www.Sartomer.arkema.com

Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex France www.Sartomer.arkema.com

