

TECHNICAL DATA SHEET

CN153

Epoxy Acrylate Oligomer

DESCRIPTION

CN153 is an oligomer that has both acrylate and epoxy functionality on the same backbone. The epoxy ring will readily react with amines or acids. The CN153 is mainly used in systems where dual cure is necessary to achieve a thorough cure or lower shrinkage.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	1
Color (Gd)	<5
Density at 25°C (g/mL)	1.1634

CURED PROPERTIES

Tg (°C), by DSC	26
Young Modulus (MPa)	1117
Elongation at break (%)	2.7
Tensile Strength (MPa)	26

PRODUCT PERFORMANCE

Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
PE/PET/PP/PMMA Adhesion
Flexibility
Chemical Resistance
Moisture Resistance
Shrinkage
Scratch Resistance
Abrasion Resistance

SPECIAL FEATURE

Dual cure

SUGGESTED APPLICATIONS

3D printing
Adhesives & sealants
Conformal coatings
Electronics
Flexographic inks
Inkjet inks
Offset inks
Plastic coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com