

TECHNICAL DATA SHEET

CN1968

Aliphatic Urethane Methacrylate Oligomer

Low viscosity urethane methacrylate oligomer showing good balance of tensile strength and elongation. Low color and non-yellowing performance.



No Intentionally Added Tin



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance Clear liquid Functionality Density at 25°C (g/mL) 1.0631 Color (Pt/Co or APHA) <50

CURED PROPERTIES

Elongation at break (%) 86 Tg (°C), by DSC 75

PRODUCT PERFORMANCE

Shrinkage Flexibility Wood Adhesion ABS/PC Adhesion PVC/PS Adhesion Weatherability PE/PET/PP/PMMA Adhesion Metal Adhesion Chemical Resistance

SUGGESTED APPLICATIONS

Adhesives & sealants Nail varnishes

Arkema Inc 502 Thomas Jones Way Exton, PA 19341 – AMERICA

Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex France www.Sartomer.arkema.com



