SARTOMER®

TECHNICAL DATA SHEET

CN2003

Modified Epoxy Acrylate Oligomer

DESCRIPTION

CN2003 is a modified epoxy acrylate oligomer that imparts flexibility, excellent adhesion, and low shrinkage to UV/EB-curable coating, ink, and adhesive applications. CN2003 can be used on a variety of substrates, including plastics, metals, and wood.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance Clear liquid
Functionality 2
Color (Gd) <4
Density at 25°C (g/mL) 1.1835
Refractive Index at 25°C 1.5304

CURED PROPERTIES

Tg (°C), by DSC 58
Young Modulus (MPa) 97
Elongation at break (%) 70
Tensile Strength (MPa) 6

PRODUCT PERFORMANCE

Metal Adhesion Chemical Resistance Moisture Resistance Corrosion Resistance Shrinkage Wood Adhesion ABS/PC Adhesion PVC/PS Adhesion PE/PET/PP/PMMA Adhesion Flexibility Stain Resistance

SPECIAL FEATURE

Adhesion promoter

SUGGESTED APPLICATIONS

Metal coatings Screen inks Wood coatings

Arkema Inc 502 Thomas Jones Way Exton, PA 19341 – AMERICA www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com

