

TECHNICAL DATA SHEET

CN296

Polyester Acrylate

DESCRIPTION

CN296 is a hexafunctional polyester acrylate oligomer that demonstrates good pigment wetting and fast cure in lithographic and flexographic inks and abrasion resistant coatings.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	6
Color (Gd)	<16
Density at 25°C (g/mL)	1.0701
Refractive Index at 25°C	1.489

CURED PROPERTIES

Tg (°C), by DSC	37
Young Modulus (MPa)	255
Elongation at break (%)	5
Tensile Strength (MPa)	28

PRODUCT PERFORMANCE

Wood Adhesion
Hardness
Moisture Resistance
Corrosion Resistance
Flexibility
Scratch Resistance
Abrasion Resistance
Stain Resistance
Chemical Resistance

SPECIAL FEATURE

High functionality

SUGGESTED APPLICATIONS

Flexographic inks
Inkjet inks

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com