

TECHNICAL DATA SHEET

CN9010

Aliphatic Urethane Acrylate Oligomer

DESCRIPTION

CN9010 is an aliphatic urethane acrylate oligomer developed for UV/EB-cured coatings and inks. CN9010 imparts hardness, very fast cure response, and non-yellowing characteristics to these applications.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	6
Color (Pt/Co or APHA)	<100
Density at 25°C (g/mL)	1.2045
Refractive Index at 25°C	1.495
Surface Tension at 20°C (mN/m)	37

CURED PROPERTIES

Tg (°C), by DSC	103
Elongation at break (%)	3
Tensile Strength (MPa)	30
Young Modulus (MPa)	607

PRODUCT PERFORMANCE

Hardness
Weatherability
Stain Resistance
Abrasion Resistance
Chemical Resistance
Scratch Resistance
Moisture Resistance
Corrosion Resistance

SPECIAL FEATURE

High functionality

SUGGESTED APPLICATIONS

Adhesives & sealants
Electronics
Flexographic inks
Inkjet inks

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com