

TECHNICAL DATA SHEET

CN9030

Aliphatic Urethane Acrylate Oligomer

DESCRIPTION

CN9030 is a urethane acrylate oligomer designed to produce tough, weather resistant UV/EB-cure coatings.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Density at 25°C (g/mL)	1.1213
Refractive Index at 25°C	1.483
Color (Pt/Co or APHA)	<100

CURED PROPERTIES

Young Modulus (MPa)	262
Elongation at break (%)	125
Tensile Strength (MPa)	31

PRODUCT PERFORMANCE

Weatherability
Hardness
Stain Resistance
Chemical Resistance
Shrinkage
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
PE/PET/PP/PMMA Adhesion
Corrosion Resistance
Wood Adhesion
Abrasion Resistance
Moisture Resistance

SPECIAL FEATURE

Tough

SUGGESTED APPLICATIONS

Adhesives & sealants
Inkjet inks
Metal coatings
Screen inks
Wood coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com