

TECHNICAL DATA SHEET

CN9039

Aliphatic Urethane Acrylate Oligomer

CN9039 is an oligomer that offers low viscosity, good abrasion and heat resistance.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Clear liquid Functionality Color (Pt/Co or APHA) <100 Density at 25°C (g/mL) 1.1835 Refractive Index at 25°C 1.49

CURED PROPERTIES

Tg (°C), by DSC 145 Elongation at break (%) Tensile Strength (MPa) 76 Young Modulus (MPa) 3344

PRODUCT PERFORMANCE

Hardness Stain Resistance Weatherability Abrasion Resistance Chemical Resistance Scratch Resistance Moisture Resistance Corrosion Resistance

SPECIAL FEATURE

High functionality

SUGGESTED APPLICATIONS

Adhesives & sealants Inkjet inks Wood coatings

Arkema Inc 502 Thomas Jones Way Exton, PA 19341 – AMERICA www.Sartomer.arkema.com

Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex France www.Sartomer.arkema.com

