

TECHNICAL DATA SHEET

CN9070

Aliphatic Urethane Acrylate Oligomer

DESCRIPTION

CN9070 is a hydrophobic oligomer based off of an aliphatic hydrophobic backbone. The oligomer possesses good resistance to water, both liquid and vapor, and to various chemicals. Upon crosslinking, the CN9070 will have a low Tg, low crosslink density, and will be flexible.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Density at 25°C (g/mL)	0.8966
Refractive Index at 25°C	1.472
Surface Tension at 20°C (mN/m)	30
Functionality	2
Color (Pt/Co or APHA)	<50

CURED PROPERTIES

Tg (°C), by DSC	-48
Young Modulus (MPa)	1
Elongation at break (%)	65

PRODUCT PERFORMANCE

Shrinkage
Flexibility
Weatherability
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
Moisture Resistance
Corrosion Resistance
PE/PET/PP/PMMA Adhesion

SPECIAL FEATURE

Hydrophobic

SUGGESTED APPLICATIONS

Adhesives & sealants
Electronics

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com