

TECHNICAL DATA SHEET

CN963

Urethane Acrylate

DESCRIPTION

CN963 is a difunctional urethane acrylate used in UV/EB applications.



LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Color (Pt/Co or APHA)	<100

PRODUCT PERFORMANCE

SUGGESTED APPLICATIONS

Adhesives & sealants  
Electronics  
Metal coatings  
Nail varnishes  
Plastic coatings  
Wood coatings

SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

Arkema Inc  
502 Thomas Jones Way  
Exton, PA 19341 – AMERICA  
[www.Sartomer.arkema.com](http://www.Sartomer.arkema.com)

Arkema France  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex  
France  
[www.Sartomer.arkema.com](http://www.Sartomer.arkema.com)