

## TECHNICAL DATA SHEET

# CN970A60

Aromatic Urethane Acrylate blended with TPGDA (SR306)

### DESCRIPTION

CN970A60 is an aromatic polyether based urethane triacrylate oligomer blended with 40% SR306, tripropylene glycol diacrylate. It is a hard oligomer.



### SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

### STORAGE

See SDS for Storage Considerations

### HEALTH AND SAFETY

See SDS for Health & Safety Considerations

### LIQUID PROPERTIES

Functionality	3
Appearance	Clear liquid
Refractive Index at 25°C	1.5005
Density at 25°C (g/mL)	1.1434
Color (Pt/Co or APHA)	<100

### CURED PROPERTIES

Tg (°C), by DSC	57
Young Modulus (MPa)	1120
Elongation at break (%)	4
Tensile Strength (MPa)	34

### PRODUCT PERFORMANCE

Shrinkage  
Hardness  
Pigment Wetting  
Wood Adhesion  
Corrosion Resistance  
Scratch Resistance  
Abrasion Resistance

### SUGGESTED APPLICATIONS

Flexographic inks  
Inkjet inks  
Metal coatings  
Wood coatings

**Arkema Inc**  
502 Thomas Jones Way  
Exton, PA 19341 – AMERICA  
[www.Sartomer.arkema.com](http://www.Sartomer.arkema.com)

**Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex  
France  
[www.Sartomer.arkema.com](http://www.Sartomer.arkema.com)