

### TECHNICAL DATA SHEET

# CN972

## Aromatic Urethane Acrylate

#### **DESCRIPTION**

CN972 is an aromatic polyether based urethane triacrylate oligomer. It is a flexible oligomer.



## **SHELF LIFE**

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

#### **STORAGE**

See SDS for Storage Considerations

#### **HEALTH AND SAFETY**

See SDS for Health & Safety Considerations

## **LIQUID PROPERTIES**

Appearance Clear liquid
Density at 25°C (g/mL) 1.0551
Refractive Index at 25°C 1.4811
Functionality 3
Color (Pt/Co or APHA) <100

#### **CURED PROPERTIES**

Tg (°C), by DSC -47
Young Modulus (MPa) 7
Elongation at break (%) 17
Tensile Strength (MPa) 1

#### **PRODUCT PERFORMANCE**

Shrinkage Flexibility Wood Adhesion Pigment Wetting Metal Adhesion Corrosion Resistance

#### **SUGGESTED APPLICATIONS**

Adhesives & sealants
Electrical potting & encapsulation
Electronics
Flexographic inks
Industrial flooring & waterproofing
Inkjet inks
Metal coatings
Overprint varnishes
Wood coatings

Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80 www.Sartomer.arkema.com

