

TECHNICAL DATA SHEET

CN9782

Aromatic Urethane Acrylate

DESCRIPTION

CN9782 is a difunctional aromatic urethane acrylate oligomer that produces tough, flexible, and abrasion resistant radiation-cured films. CN9782 is especially recommended for plastic, textile, leather, wood and metal coatings.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Color (Pt/Co or APHA)	<50
Density at 25°C (g/mL)	1.1895
Refractive Index at 25°C	1.49

CURED PROPERTIES

Tg (°C), by DSC	-32
Elongation at break (%)	365
Tensile Strength (MPa)	8
Young Modulus (MPa)	2

PRODUCT PERFORMANCE

Flexibility
Pigment Wetting
Shrinkage
Wood Adhesion
Metal Adhesion
Moisture Resistance
Corrosion Resistance

SPECIAL FEATURE

Tough

SUGGESTED APPLICATIONS

Adhesives & sealants
Metal coatings
Wood coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com