

## TECHNICAL DATA SHEET

### CN991

#### Aliphatic Urethane Acrylate

##### DESCRIPTION

CN991 is a polyester based urethane diacrylate oligomer with low viscosity and excellent conformal properties. CN991 is especially suited to outdoor applications.



Most suitable for EB curing



Superior weathering performance



##### SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

##### STORAGE

See SDS for Storage Considerations

##### HEALTH AND SAFETY

See SDS for Health & Safety Considerations

##### LIQUID PROPERTIES

Appearance	Clear liquid
Density at 25°C (g/mL)	1.1072
Refractive Index at 25°C	1.488
Surface Tension at 20°C (mN/m)	37.3
Functionality	2
Color (Pt/Co or APHA)	<100

##### CURED PROPERTIES

Elongation at break (%)	15
Tensile Strength (MPa)	37

##### PRODUCT PERFORMANCE

Shrinkage  
Weatherability  
Flexibility  
Wood Adhesion  
ABS/PC Adhesion  
Metal Adhesion  
PVC/PS Adhesion  
Scratch Resistance  
Abrasion Resistance  
Moisture Resistance  
Corrosion Resistance  
PE/PET/PP/PMMA Adhesion

##### SUGGESTED APPLICATIONS

Adhesives & sealants  
Electronics  
Flexographic inks  
Inkjet inks  
Metal coatings  
Optical fibers  
Overprint varnishes  
Screen inks