

TECHNICAL DATA SHEET

SR150

Ethoxylated Bisphenol A Dimethacrylate

DESCRIPTION

SR150 is a low volatility monomer used in free radical polymerization. It provides a good hydrophobic and hydrophilic balance.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Color (Pt/Co or APHA)	<50
Density at 25°C (g/mL)	1.1253
Refractive Index at 25°C	1.532
Surface Tension at 20°C (mN/m)	39
Viscosity at 25°C (mPa.s or cPs)	700

PRODUCT PERFORMANCE

Wood Adhesion
Corrosion Resistance
Shrinkage
Flexibility
Chemical Resistance
Moisture Resistance

SUGGESTED APPLICATIONS

Adhesives & sealants
Artificial marble
Composites
Electrical potting & encapsulation
Flexographic inks
Industrial flooring & waterproofing
Rubber manufacturing

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex
France
www.Sartomer.arkema.com