

TECHNICAL DATA SHEET

SR9009

Methacrylate ester

DESCRIPTION

SR9009 is a trifunctional methacrylate having excellent adhesion and fast cure response. Adhesion promoter at 5-10%



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Viscosity at 25°C (mPa.s or cPs)	35
Density at 25°C (g/mL)	1.0691
Refractive Index at 25°C	1.472
Functionality	3
Color (Pt/Co or APHA)	<300

CURED PROPERTIES

Tg (°C), by DSC	43
-----------------	----

PRODUCT PERFORMANCE

Hardness
Weatherability
Scratch Resistance
Abrasion Resistance
Chemical Resistance
Moisture Resistance
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
Stain Resistance
Corrosion Resistance
PE/PET/PP/PMMA Adhesion

SPECIAL FEATURE

Adhesion promoter

SUGGESTED APPLICATIONS

Adhesives & sealants
Metal coatings

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com