

TECHNICAL DATA SHEET

CN2603

Acrylic Ester

DESCRIPTION

CN2603 is a high refractive index, halogen-free oligomer developed for UV/EB-cured applications.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

| | |
|----------------------------------|--------------|
| Appearance | Clear liquid |
| Functionality | 2 |
| Color (Pt/Co or APHA) | <250 |
| Density at 25°C (g/mL) | 1.1393 |
| Refractive Index at 25°C | 1.5484 |
| Viscosity at 25°C (mPa.s or cPs) | 12500 |

CURED PROPERTIES

| | |
|-----------------|----|
| Tg (°C), by DSC | 23 |
|-----------------|----|

PRODUCT PERFORMANCE

Hardness
Stain Resistance
Scratch Resistance
Abrasion Resistance
Chemical Resistance
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
Moisture Resistance
Corrosion Resistance
PE/PET/PP/PMMA Adhesion

SUGGESTED APPLICATIONS

Adhesives & sealants
Wood coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com