

TECHNICAL DATA SHEET

CN2262

Polyester Acrylate

DESCRIPTION

CN2262 is a polyester acrylate oligomer with a Primary Irritation Index (PII) of zero. CN2262 was developed for sprayable UV curable wood coatings applications where hardness and abrasion resistance are required. CN2262 demonstrates excellent cure rates and in-tra-coat adhesion.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	4
Color (Pt/Co or APHA)	<200
Viscosity at 25°C (mPa.s or cPs)	500
Density at 25°C (g/mL)	1.1032
Refractive Index at 25°C	1.457
Surface Tension at 20°C (mN/m)	35

CURED PROPERTIES

Tg (°C), by DSC	31
Young Modulus (MPa)	434
Elongation at break (%)	10
Tensile Strength (MPa)	29

PRODUCT PERFORMANCE

Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
Scratch Resistance
Abrasion Resistance
PE/PET/PP/PMMA Adhesion
Hardness
Shrinkage
Chemical Resistance
Moisture Resistance
Flexibility
Stain Resistance

SUGGESTED APPLICATIONS

Flexographic inks
Overprint varnishes
Wood coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com