SARTOMER®

TECHNICAL DATA SHEET

CN973J75

Aromatic Urethane Acrylate blended with IBOA (SR506)

CN973J75 is an aromatic polyester based urethane diacrylate oligomer blended with 25% SR506, isobornyl acrylate. It is a highly flexible oligomer.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical she-If-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Clear liquid Functionality Density at 25°C (g/mL) 1.0731 Refractive Index at 25°C 1.4777 Color (Pt/Co or APHA) <100

CURED PROPERTIES

Young Modulus (MPa) Elongation at break (%) 279 Tensile Strength (MPa) Tg (°C), by DSC -31

PRODUCT PERFORMANCE

Flexibility Metal Adhesion ABS/PC Adhesion PVC/PS Adhesion PE/PET/PP/PMMA Adhesion Shrinkage Wood Adhesion Chemical Resistance Corrosion Resistance Weatherability Moisture Resistance

SUGGESTED APPLICATIONS

Adhesives & sealants Electronics Flexographic inks Inkjet inks Metal coatings Overprint varnishes Plastic coatings Wood coatings

Arkema Inc www.Sartomer.arkema.com

Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80 www.Sartomer.arkema.com

