

TECHNICAL DATA SHEET

CN964A85

Aliphatic Urethane Acrylate blended with TPGDA (SR306)

DESCRIPTION

CN964A85 is an aliphatic polyester based urethane diacrylate oligomer blended with 15% SR306, tripropylene glycol diacrylate. It is a resilient oligomer offering good weatherability.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Density at 25°C (g/mL)	1.0922
Refractive Index at 25°C	1.48
Color (Pt/Co or APHA)	<100

CURED PROPERTIES

Young Modulus (MPa)	75
Elongation at break (%)	38
Tensile Strength (MPa)	8
Tg (°C), by DSC	-14

PRODUCT PERFORMANCE

Weatherability
Metal Adhesion
ABS/PC Adhesion
PVC/PS Adhesion
PE/PET/PP/PMMA Adhesion
Shrinkage
Wood Adhesion
Hardness
Flexibility
Stain Resistance
Chemical Resistance
Corrosion Resistance
Abrasion Resistance
Moisture Resistance

SUGGESTED APPLICATIONS

Adhesives & sealants
Electronics
Flexographic inks
Inkjet inks
Screen inks
Wood coatings

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com