

TECHNICAL DATA SHEET

CN9018

Aliphatic Urethane Acrylate Oligomer

CN9018 has been developed for UV/EB-cured laminating and pressure-sensitive adhesives. CN9018 imparts excellent adhesion, flexibility, and water resistance to laminating and pressure-sensitive adhesive formulations - especially those for glass.



Superior weathering performance



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance Clear liquid Functionality Color (Gd) Density at 25°C (g/mL) 0.9999

CURED PROPERTIES

Tg (°C), by DSC -55 Young Modulus (MPa)

PRODUCT PERFORMANCE

Flexibility Shrinkage Weatherability Wood Adhesion ABS/PC Adhesion Metal Adhesion PVC/PS Adhesion Chemical Resistance Moisture Resistance Corrosion Resistance PE/PET/PP/PMMA Adhesion

SPECIAL FEATURE

Adhesion promoter

SUGGESTED APPLICATIONS

Adhesives & sealants Flexographic inks

Arkema Inc Exton, PA 19341 - AMERICA www.Sartomer.arkema.com

Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80 www.Sartomer.arkema.com

