

TECHNICAL DATA SHEET

CN9023

Aliphatic Urethane Acrylate

DESCRIPTION

CN9023 is a difunctional aliphatic urethane acrylate oligomer characterized by low color and low viscosity. It is non-yellowing and imparts softness and flexibility to adhesives, coatings, and inks.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Functionality	2
Color (Pt/Co or APHA)	15
Density at 25°C (g/mL)	1.026
Refractive Index at 25°C	1.459

CURED PROPERTIES

Tg (°C), by DSC	-62
Young Modulus (MPa)	3
Elongation at break (%)	61
Tensile Strength (MPa)	1

PRODUCT PERFORMANCE

Flexibility
Pigment Wetting
Weatherability
Moisture Resistance
Shrinkage
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
Stain Resistance
Chemical Resistance
Corrosion Resistance
PE/PET/PP/PMMA Adhesion

SUGGESTED APPLICATIONS

Adhesives & sealants
Inkjet inks
Nail varnishes

Arkema Inc
502 Thomas Jones Way
Exton, PA 19341 – AMERICA
www.Sartomer.arkema.com

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com