

TECHNICAL DATA SHEET

CN973H85

Aromatic Urethane Acrylate blended with EOEOEA (SR256)

DESCRIPTION

CN973H85 is an aromatic polyester based urethane diacrylate oligomer blended with 15% SR256, 2(2-ethoxyethoxy) ethyl acrylate. It is a highly flexible oligomer.



SHELF LIFE

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical shelf-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

STORAGE

See SDS for Storage Considerations

HEALTH AND SAFETY

See SDS for Health & Safety Considerations

LIQUID PROPERTIES

Appearance	Clear liquid
Density at 25°C (g/mL)	1.0741
Refractive Index at 25°C	1.4784
Functionality	3
Color (Pt/Co or APHA)	<100

CURED PROPERTIES

Tg (°C), by DSC	-36
Young Modulus (MPa)	2
Elongation at break (%)	122
Tensile Strength (MPa)	1

PRODUCT PERFORMANCE

Shrinkage
Flexibility
Wood Adhesion
ABS/PC Adhesion
Metal Adhesion
PVC/PS Adhesion
PE/PET/PP/PMMA Adhesion
Weatherability
Chemical Resistance
Moisture Resistance
Corrosion Resistance

SUGGESTED APPLICATIONS

Adhesives & sealants
Electronics
Flexographic inks
Inkjet inks
Metal coatings
Overprint varnishes
Plastic coatings
Wood coatings

Headquarter: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80
www.Sartomer.arkema.com