# **SARTOMER®**

### TECHNICAL DATA SHEET

# CN9782

### Aromatic Urethane Acrylate

CN9782 is a difunctional aromatic urethane acrylate oligomer that produces tough, flexible, and abrasion resistant radiation-cured films. CN9782 is especially recommended for plastic, textile, leather, wood and metal coatings.



#### **SHELF LIFE**

Store in the original, closed container in a dry, cool (<45°C) and well-ventilated place. Keep away from frost and heat (open flames, hot surfaces and sources of ignition) sources. Typical she-If-life is 6 months from delivery date for unopened containers. In cases where product sampling is required to carry out incoming quality tests, shelf-life should be maintained beyond opening, provided that it is tightly closed immediately after and that contamination with foreign bodies is avoided. Inhibitors have been added to enhance storage stability. They require the presence of air in the container in order to improve their efficiency. Keep stabilizer levels constant to avoid explosive polymerization. An air space is required above the liquid in all containers

#### **STORAGE**

See SDS for Storage Considerations

#### **HEALTH AND SAFETY**

See SDS for Health & Safety Considerations

## **LIQUID PROPERTIES**

Clear liquid Functionality Color (Pt/Co or APHA) <50 Density at 25°C (g/mL) 1.1895 Refractive Index at 25°C 1.49

#### **CURED PROPERTIES**

Tg (°C), by DSC -32 Young Modulus (MPa) 2 Elongation at break (%) 365 Tensile Strength (MPa)

#### **PRODUCT PERFORMANCE**

Flexibility Pigment Wetting Shrinkage Wood Adhesion Metal Adhesion Moisture Resistance Corrosion Resistance

#### **SPECIAL FEATURE**

Tough

#### **SUGGESTED APPLICATIONS**

Adhesives & sealants Metal coatings Wood coatings

Arkema Inc

Headquarter: Arkema France 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80 www.Sartomer.arkema.com

